

ITA 24

PLASTIC STRAPPING TOOL > BATTERY

Battery Strapping Tool for 13mm / 16mm - PP & PET Strap Three Operating Modes

ITA 24 is the most suitable and reliable three operating modes battery strapping tool, studied for 13mm and 16mm PP and PET strap.

Lightweight, well balanced, ergonomic and easy to be used also with one hand, ITA 24 can be used in fully automatic, semi-automatic and manual operating modes.

ITA 24 is equipped with two Brushless motors to grant low maintenance, high speed and improved electronic control.

The dedicated high efficiency and long life Lithium Polymer battery, will grant high number of duty cycles per single charge, without any memory effect on the battery.

ITA 24 uses friction weld seal technology that guarantees high seal efficiency, without requiring any seal.

The tool finds application in many fields, from the timber to the corrugated, from the steel to the logistic to the brick or for any possible other strapping application.

ITA 24 is the battery strapping tool for plastic strap at 360°.



FEATURES

3 Operating Modes:
Automatic / Semi Automatic / Manual
Easy to be used
Digital control Panel
Brushless Motor technology

BENEFITS

Wide range & adjustable tension (300N-2500N)
Lightweight and well balanced
One hand operating tool
Easy access to wearing parts
Strong and well protected motor housing

TECHNICAL SPECIFICATION

Dimensions	300 x 150 x 160 mm 11.8" x 5.9" x 6.3"
Weight (with battery)	4.3 Kg - 9.5 lbs
STRAP	
Type	PP and PET Strap
Width	13mm / 16mm (1/2" - 5/8")
Thickness	0,5mm - 1,05mm (0.019"-0.04")
POWER SUPPLY	
Battery	Li-Po 14.8V – 2.2Ah
PERFORMANCE	
Min. tension force	300 N
Max. tension force	2500 N
Tensioning speed	10-16 mt/m
Sealing	Friction weld seal
Joint Strength	75% of breaking strength

* variable according to strap type

MODEL

CODE	DESCRIPTION
T2499971	ITA 24 + 1 Battery + 1 Battery Charger
T2499972	ITA 24 + 2 Batteries + 1 Battery Charger
T2499973	ITA 24 + 3 Batteries + 1 Battery Charger